



## **POOL TILE GROUT REPAIR KIT**

A Do It Yourself Pool Patch Repair Kit

### **POOL PATCH INSTRUCTIONS**

- 1.** Lower pool water 4" below tile repair area.
- 2.** Remove existing loose material and grout.
- 3.** Add 2 oz. of LIQUID CEMENT BONDER per 1½ lb. of DRY POOL PATCH GROUT MIX.  
Add water and mix until a putty consistency is achieved.
- 4.** Apply GROUT MIX filling in pool tile area to be grouted and allow to dry for 5 minutes.
- 5.** Use a damp sponge and lightly wipe off excess pool tile grout to a smooth joint.
- 6.** Allow to dry 2 hours then wipe off remaining film with dry soft cloth.

### **ALLOW TO CURE 4 HOURS BEFORE FILLING POOL**

**WARNING:** Contains Cement, an Alkaline substance irritating to eyes and skin. Contains Acrylic Resin Cement Bonder. Should product contact eyes, flush them immediately and repeatedly with water and call a Physician. **DO NOT TAKE INTERNALLY.** In case of skin contact, rinse immediately with water. **USE OF RUBBER GLOVES AND EYE PROTECTION IS RECOMMENDED.**

**KEEP OUT OF REACH OF CHILDREN**

Pool Patch, Phoenix, Arizona  
**poolpatch.com**