



WHITE POOL PLASTER REPAIR KIT

A Do It Yourself Pool Patch Repair Kit

POOL PATCH INSTRUCTIONS

1. Lower water below repair area.
2. Remove loose cement and chip area down a minimum of a ¼ inch deep.
3. Add 2 oz. of LIQUID CEMENT BONDER per 1½ lb. of DRY POOL PATCH CEMENT MIX. Add water and mix until a putty consistency is achieved.
- 4a. CRACK REPAIRS - Apply POOL PATCH into crack and wipe off excess material with a moist sponge.
- 4b. CHIPS & LARGER AREAS -Trowel POOL PATCH firmly filling the area. Trowel till patch is smooth and flat. Remove excess from edges with a moist sponge. After POOL PATCH stiffens, trowel again with a moist trowel until area is flat and smooth.

ALLOW TO CURE HARD BEFORE FILLING POOL

WARNING:

Contains Cement, an Alkaline substance irritating to eyes and skin. Contains Acrylic Resin Cement Bonder. Should product contact eyes, flush them immediately and repeatedly with water and call a Physician. **DO NOT TAKE INTERNALLY.** In case of skin contact, rinse immediately with water. **USE OF RUBBER GLOVES AND EYE PROTECTION IS RECOMMENDED.**

KEEP OUT OF REACH OF CHILDREN

Pool Patch, Phoenix, Arizona
poolpatch.com