



## **POOL TILE SETTING REPAIR KIT**

A Do It Yourself Pool Patch Repair Kit

### **POOL PATCH INSTRUCTIONS**

- 1.** Lower pool water 4" below tile repair area.
- 2.** Remove existing material from tile repair area.
- 3.** Check surface area with tile to be certain it will install flush prior to setting.
- 4.** Add water to SETTING MIX and mix until a putty consistency is achieved.
- 5.** Apply SETTING MIX with a 1/4" notched trowel to the back of the pool tile or to the surface, push pool tile into position flush with existing tile surface. If pool tile is not setting flush remove excess SETTING MIX to achieve flush installation.
- 6.** Allow for pool tile to dry before applying POOL PATCH GROUT REPAIR.

### **ALLOW TO CURE 4 HOURS BEFORE FILLING POOL**

**WARNING:** Contains Cement, an Alkaline substance irritating to eyes and skin. Should product contact eyes, flush them immediately and repeatedly with water and call a Physician. **DO NOT TAKE INTERNALLY.** In case of skin contact, rinse immediately with water. **USE OF RUBBER GLOVES AND EYE PROTECTION IS RECOMMENDED.**

**KEEP OUT OF REACH OF CHILDREN**

Pool Patch, Phoenix, Arizona  
**poolpatch.com**