



POOL TILE GROUT REPAIR KIT

A Do It Yourself Pool Patch Repair Kit

POOL PATCH INSTRUCTIONS

1. Lower pool water 4" below tile repair area.
2. Remove existing loose material and grout.
3. Add 2 oz. of LIQUID CEMENT BONDER per 1½ lb. of DRY POOL PATCH GROUT MIX.
Add water and mix until a putty consistency is achieved.
4. Apply GROUT MIX filling in pool tile area to be grouted and allow to dry for 5 minutes.
5. Use a damp sponge and lightly wipe off excess pool tile grout to a smooth joint.
6. Allow to dry 2 hours then wipe off remaining film with dry soft cloth.

ALLOW TO CURE 4 HOURS BEFORE FILLING POOL

WARNING: Contains Cement, an Alkaline substance irritating to eyes and skin. Contains Acrylic Resin Cement Bonder. Should product contact eyes, flush them immediately and repeatedly with water and call a Physician. **DO NOT TAKE INTERNALLY.** In case of skin contact, rinse immediately with water. **USE OF RUBBER GLOVES AND EYE PROTECTION IS RECOMMENDED.**

KEEP OUT OF REACH OF CHILDREN

Pool Patch, Phoenix, Arizona
poolpatch.com